



**WORKGard® FULL BODY HARNESS WITH DORSAL ANCHORAGE POINT (TÜV SÜD PSB)**

WORKGard® HARNESES

- Polyester webbing in high visibility yellow/black
- Harness with dorsal anchorage point
- Separate adjustment for leg straps
- Body height adjustment
- Tested and approved to EN361 and SS528:Part 1 standards (TÜV SÜD PSB-approved)

**PRODUCT CODE**

<b>710WGF501</b>	WORKGard® Full Body Harness with Dorsal Anchorage Point (TÜV SÜD PSB-approved)
------------------	--



**WORKGard® FULL BODY HARNESS WITH FRONT AND DORSAL ANCHORAGE POINT (TÜV SÜD PSB)**

- Polyester webbing in high visibility green/black
- Harness with front and dorsal anchorage points
- Separate adjustment for leg straps
- Body height adjustment
- Tested and approved to EN361 and SS528:Part 1 standards (TÜV SÜD PSB-approved)

**PRODUCT CODE**

<b>710WGF502</b>	WORKGard® Full Body Harness with Front and Dorsal Anchorage Point (TÜV SÜD PSB-approved)
------------------	--



**WORKGard® ENERGY ABSORBER WITH DOUBLE ROPE SAFETY LANYARD (TÜV SÜD PSB)**

WORKGard® LANYARDS

- Polyamide rope and energy absorber
- Maximum length: 2 x 1.8m
- Diameter: 12mm
- Includes 2 hot-dipped galvanized steel connecting scaffold hooks (opening: 50mm) and steel twist-lock karabiner (certified according to EN362 & SS528:Part 5 standards)
- Tested and approved to EN355, EN354 and SS528:Part 2 standards (TÜV SÜD PSB-approved)

**PRODUCT CODE**

<b>710WGF602</b>	WORKGard® Energy Absorber with Double Rope Safety Lanyard, 2 Scaffold Hooks, Twist-lock Karabiner (TÜV SÜD PSB-approved)
------------------	--



**WORKGard® ENERGY ABSORBER WITH SINGLE ROPE SAFETY LANYARD (TÜV SÜD PSB)**

- Polyamide rope and energy absorber
- Maximum length: 1.8m
- Diameter: 12mm
- Includes hot-dipped galvanized steel connecting scaffold hook (opening: 50mm) and steel twist-lock karabiner (certified according to EN362 & SS528:Part 5 standards)
- Tested and approved to EN355, EN354 and SS528:Part 2 standards (TÜV SÜD PSB-approved)

**PRODUCT CODE**

<b>710WGF601</b>	WORKGard® Energy Absorber with Single Rope Safety Lanyard, Scaffold Hook, Twist-lock Karabiner (TÜV SÜD PSB-approved)
------------------	---



**WORKGard® SINGLE ROPE CONNECTING LANYARD**

- Polyamide rope and energy absorber
- Maximum length: 2m
- Diameter: 12mm
- Includes hot-dipped galvanized steel connecting scaffold hook (opening: 50mm) and steel twist-lock karabiner (certified according to EN362 standards)
- Suitable only for fall restraint, not for fall arrest
- Tested and approved to EN354 standards

**PRODUCT CODE**

<b>710WGF603</b>	WORKGard® Single Rope Connecting Lanyard, Scaffold Hook, Twist-lock Karabiner
------------------	---

