



WORKGard® FULL BODY HARNESS WITH DORSAL ANCHORAGE POINT (TÜV SÜD PSB)

WORKGard® HARNESES

- Polyester webbing in high visibility yellow/black
- Harness with dorsal anchorage point
- Separate adjustment for leg straps
- Body height adjustment
- Tested and approved to EN361 and SS528:Part 1 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WGF501	WORKGard® Full Body Harness with Dorsal Anchorage Point (TÜV SÜD PSB-approved)
------------------	--------------------------------------------------------------------------------



WORKGard® FULL BODY HARNESS WITH FRONT AND DORSAL ANCHORAGE POINT (TÜV SÜD PSB)

- Polyester webbing in high visibility green/black
- Harness with front and dorsal anchorage points
- Separate adjustment for leg straps
- Body height adjustment
- Tested and approved to EN361 and SS528:Part 1 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WGF502	WORKGard® Full Body Harness with Front and Dorsal Anchorage Point (TÜV SÜD PSB-approved)
------------------	------------------------------------------------------------------------------------------



WORKGard® ENERGY ABSORBER WITH DOUBLE ROPE SAFETY LANYARD (TÜV SÜD PSB)

WORKGard® LANYARDS

- Polyamide rope and energy absorber
- Maximum length: 2 x 1.8m
- Diameter: 12mm
- Includes 2 hot-dipped galvanized steel connecting scaffold hooks (opening: 50mm) and steel twist-lock karabiner (certified according to EN362 & SS528:Part 5 standards)
- Tested and approved to EN355, EN354 and SS528:Part 2 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WGF602	WORKGard® Energy Absorber with Double Rope Safety Lanyard, 2 Scaffold Hooks, Twist-lock Karabiner (TÜV SÜD PSB-approved)
------------------	--------------------------------------------------------------------------------------------------------------------------



WORKGard® ENERGY ABSORBER WITH SINGLE ROPE SAFETY LANYARD (TÜV SÜD PSB)

- Polyamide rope and energy absorber
- Maximum length: 1.8m
- Diameter: 12mm
- Includes hot-dipped galvanized steel connecting scaffold hook (opening: 50mm) and steel twist-lock karabiner (certified according to EN362 & SS528:Part 5 standards)
- Tested and approved to EN355, EN354 and SS528:Part 2 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WGF601	WORKGard® Energy Absorber with Single Rope Safety Lanyard, Scaffold Hook, Twist-lock Karabiner (TÜV SÜD PSB-approved)
------------------	-----------------------------------------------------------------------------------------------------------------------



WORKGard® SINGLE ROPE CONNECTING LANYARD

- Polyamide rope and energy absorber
- Maximum length: 2m
- Diameter: 12mm
- Includes hot-dipped galvanized steel connecting scaffold hook (opening: 50mm) and steel twist-lock karabiner (certified according to EN362 standards)
- Suitable only for fall restraint, not for fall arrest
- Tested and approved to EN354 standards

PRODUCT CODE

710WGF603	WORKGard® Single Rope Connecting Lanyard, Scaffold Hook, Twist-lock Karabiner
------------------	-------------------------------------------------------------------------------

