



WORKSafe® WSF120 FULL BODY HARNESS WITH FRONT AND DORSAL ANCHORAGE POINTS (TÜV SÜD PSB)

- Harness with front and dorsal anchorage points
- Separate adjustment for leg straps
- Body height adjustment
- Tested to EN361 and SS528: Part 1 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WSF120	WORKSafe® Full Body Harness with Front, Dorsal Anchorage Points (TÜV SÜD PSB-approved)
------------------	--

WORKSafe® BASIC HARNESSES



WORKSafe® WSF110C FULL BODY HARNESS WITH DORSAL ANCHORAGE POINT (TÜV SÜD PSB)

- Harness with dorsal anchorage point
- Separate adjustment for leg straps
- Body height adjustment
- Tested to EN361 and SS528: Part 1 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WSF110C	WORKSafe® Full Body Harness with Dorsal Anchorage Point (TÜV SÜD PSB-approved)
-------------------	--



WORKSafe® WSFAB110-01 FULL BODY HARNESS WITH DORSAL ANCHORAGE POINT (TÜV SÜD PSB)

- Harness with dorsal anchorage point
- Separate adjustment for leg and shoulder straps
- Body height adjustment
- Tested to EN361 and SS528: Part 1 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WSFAB110-01	WORKSafe® Full Body Harness with Dorsal Anchorage Point (TÜV SÜD PSB-approved)
-----------------------	--



WORKSafe® WSFAB130-01 FULL BODY HARNESS WITH FRONT AND DORSAL ANCHORAGE POINTS (TÜV SÜD PSB)

- Harness with front and dorsal anchorage points
- Separate adjustment for leg and shoulder straps
- Body height adjustment
- Tested to EN361 and SS528: Part 1 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WSFAB130-01	WORKSafe® Full Body Harness with Front, Dorsal Anchorage Points \ (TÜV SÜD PSB-approved)
-----------------------	--



WORKSafe® WSFAB141-01 FULL BODY HARNESS WITH FRONT AND DORSAL ANCHORAGE POINTS

- Harness with front and dorsal anchorage points
- Separate adjustment for leg and shoulder straps
- Tested and approved to EN361 standards
- Stainless steel buckles

PRODUCT CODE

710WSFAB141-01	WORKSafe® Full Body Harness with Front, Dorsal Anchorage Points, Stainless Steel Buckles
-----------------------	--





WORKSafe® BASIC HARNESSSES




- Work Positioning Belt with 2 side attaching D-rings
- Tested and approved to EN358 standards

PRODUCT CODE

710WSFAP010	WORKSafe® Work Positioning Belt, 2 Side D-Rings
--------------------	---



WORKSafe® PREMIUM HARNESSSES




- Designed for person weighing up to 140kg
- Harness with front and dorsal anchorage points, attachment point for sitting position, side attachment point for work positioning and an additional back attachment point
- Separate adjustment for leg and shoulder straps
- Comes with shoulder padding and accessories attachment on the work positioning belt
- Tested and approved to EN358, EN361 and EN813 standards

PRODUCT CODE

710WSFAB190-01XXL	WORKSafe® Full Body Harness with Front, Dorsal Anchorage Points, Work Positioning Belt, Size: XXL
--------------------------	---



WORKSafe® WSFAB190-01 FULL BODY HARNESS WITH FRONT, DORSAL ANCHORAGE POINTS, AND WORK POSITIONING BELT




- Harness with front and dorsal anchorage points and work positioning belt
- Separate adjustment for leg and shoulder straps
- Tested and approved to EN361, EN358 and EN813 standards

PRODUCT CODE

710WSFAB170-01	WORKSafe® Full Body Harness with Front, Dorsal Anchorage Points, Work Positioning Belt, 2 Side D-Rings
-----------------------	--



WORKSafe® WSFAB170-01 FULL BODY HARNESS WITH FRONT, DORSAL ANCHORAGE POINTS, AND WORK POSITIONING BELT



- Harness with front and dorsal anchorage points and work positioning belt
- Separate adjustment for leg and shoulder straps
- Tested and approved to EN361 and EN358 standards

PRODUCT CODE

710WSFAB150-01	WORKSafe® Full Body Harness with Front, Dorsal Anchorage Points, Work Positioning Belt, 2 Side D-Rings
-----------------------	--



WORKSafe® WSFAB150-01 FULL BODY HARNESS WITH FRONT, DORSAL ANCHORAGE POINTS, AND WORK POSITIONING BELT

WORKSafe® LANYARDS



- Designed for persons weighing up to 140kg
- Y-lanyard made of tubular polyamide webbing with internal elastic core
- Energy absorber made of 45mm wide polyamide webbing
- Maximum length: 2 x 2m including connectors
- Includes 2 aluminium alloy connecting scaffold hooks
- Tested and approved to EN355, EN354 and EN362 standards

PRODUCT CODE

710WSFAF1702LE101	WORKSafe® Energy Absorber with Double Elastic Lanyard, Fitted with 2 Aluminium Scaffold Hooks
--------------------------	---





WORKSafe® WSF211 CONNECTING LANYARD

WORKSafe® LANYARDS

- Polyamide rope
- Maximum length: 2m
- Diameter: 12mm
- Equipped with scaffold hook and steel screw-gate karabiner
- Tested and approved to EN354 and EN362 standards

PRODUCT CODE

710WSF211	WORKSafe® Connecting Lanyard, Scaffold Hook, Screwgate Karabiner
------------------	--



WORKSafe® WSFBW200+LB122 ENERGY ABSORBER WITH DOUBLE ROPE SAFETY LANYARD (TÜV SÜD PSB)

- Kernmantle polyamide rope and polyamide energy absorber
- Maximum length: 2 x 2m
- Diameter: 12mm
- Includes 2 aluminium alloy connecting scaffold hooks
- PSB-approved model available
- Tested and approved to EN355, EN354, EN362 and SS528: Part 2 and Part 5 standards (TÜV SÜD PSB-approved)

- Aluminium alloy twist-lock karabiner, certified with EN362 and SS528: Part 5 standards, sold separately

PRODUCT CODE

710WSFBW200+LB122	WORKSafe® Energy Absorber with Double Rope Safety Lanyard, 2 Scaffold Hooks (TÜV SÜD PSB-approved), Twist-lock Karabiner sold separately
--------------------------	--



WORKSafe® WSF210K ENERGY ABSORBER WITH SINGLE ROPE SAFETY LANYARD (TÜV SÜD PSB)

- Polyamide rope and energy absorber
- Maximum length: 1.8m
- Diameter: 12mm
- Includes 1 hot-dipped galvanized steel scaffold hook and 1 steel twist-lock karabiner
- PSB-approved model available
- Tested and approved to EN355, EN354, EN362 and SS528: Part 2 and Part 5 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WSF210K	WORKSafe® Energy Absorber with Single Rope Safety Lanyard, 2 Scaffold Hooks, Twist-Lock Karabiner (TÜV SÜD PSB-approved)
-------------------	--



WORKSafe® WSFBW200+LB121 ENERGY ABSORBER WITH SINGLE ROPE SAFETY LANYARD (TÜV SÜD PSB)

- Kernmantle polyamide rope and polyamide energy absorber
- Maximum length: 2m
- Diameter: 12mm
- Includes aluminium alloy connecting scaffold hook
- PSB-approved model available
- Tested and approved to EN355, EN354, EN362 and SS528: Part 2 and Part 5 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WSFBW200+LB121	WORKSafe® Energy Absorber with Single Rope Safety Lanyard, Scaffold Hook (TÜV SÜD PSB-approved), Twist-lock Karabiner sold separately
--------------------------	---



WORKSafe® WSF220K ENERGY ABSORBER WITH DOUBLE ROPE SAFETY LANYARD (TÜV SÜD PSB)

- Kernmantle polyamide rope and polyamide energy absorber
- Maximum length: 2 x 1.8m
- Diameter: 12mm
- Includes 2 hot-dipped galvanized steel connecting scaffold hooks and steel twist-lock karabiner certified with EN362 and SS528: Part 5 standards
- PSB-approved model available

- Tested and approved to EN355, EN354, EN362 and SS528: Part 2 and Part 5 standards (TÜV SÜD PSB-approved)

PRODUCT CODE

710WSF220K	WORKSafe® Energy Absorber with Double Rope Safety Lanyard, 2 Scaffold Hooks, Twist-Lock Karabiner (TÜV SÜD PSB-approved)
-------------------	--





WORKSafe® FALL ARRESTERS



- Zinc galvanized steel cable of diameter 4mm
- Stainless steel ring
- High Density Thermoplastic Enclosure
- Dimensions: 208 x 85 x 280mm
- Available in variety of lengths for various job-site applications
- Includes galvanized steel swivel with aluminium snap hook and fall indicator (opening: 23mm, weight: 200g)
- Tested and approved to EN360 standards



WORKSafe® WSFCR200 STEEL CABLE RETRACTOR

PRODUCT CODE

710WSFCR200-06/10/15	WORKSafe® CR200 Steel Cable Retractor, Swivel Snap Hook, Fall Indicator, Cable Length: 6m/10m/15m
-----------------------------	---

- Available in 6m (5.10kg), 10m (5.3kg) and 15m (6.10kg)



- Zinc galvanized steel cable of diameter 4mm
- Stainless steel ring
- High Density Thermoplastic Enclosure
- Dimensions: 260 x 120 x 340mm
- Available in 20m (11.25kg) and 28m (11.65kg)
- Includes galvanized steel swivel aluminium snap hook and fall indicator (opening: 23mm, weight: 200g)
- Tested and approved to EN360 standards



WORKSafe® WSFCR300 STEEL CABLE RETRACTOR

PRODUCT CODE

710WSFCR300-20/28	WORKSafe® CR300 Steel Cable Retractor, Swivel Snap Hook, Fall Indicator, Cable Length: 20m/28m
--------------------------	--



- Energy dissipating element
- Polyamide webbing width: 45mm
- Dimensions: 96 x 98 x 320mm (without snap hook)
- Working length: 2.4m
- Weight: 1,680g
- Includes swivel galvanized steel scaffold hook (opening: 60mm) and aluminium swivel galvanized steel snap hook (opening: 24mm)
- Tested and approved to EN360 standards



WORKSafe® WSFAH220 ROLEX WEBBING RETRACTOR

PRODUCT CODE

710WSFAH220S	WORKSafe® Rolex Webbing Retractor, Swivel Scaffold Hook, Swivel Snap Hook, Energy Absorber, Webbing Length: 2.4m
---------------------	--



- Energy dissipating element
- Polyamide webbing width: 45mm
- Dimensions (without webbing and snap hook): 115 x 80 x 150mm
- Working length: 2.25m
- Weight: 1,150g
- Includes steel twist-lock karabiner, galvanized steel swivel aluminium snap hook (opening: 22mm, weight: 220g)
- Tested and approved to EN360 standards



WORKSafe® WSFAH210 ROLEX WEBBING RETRACTOR

PRODUCT CODE

710WSFAH210	WORKSafe® AH210 Rolex Webbing Retractor, Twist-lock Karabiner, Swivel Snap Hook, Energy Absorber, Webbing Length: 2.25m
--------------------	---



- Lightweight webbing retractor
- High density thermoplastic enclosure
- Dimensions: 160 x 70 x 230mm
- Working length: 6m
- Weight: 1,700g
- Includes galvanized steel screw-gate karabiner, aluminium swivel snap hook and fall indicator (opening: 24mm, weight: 220g)
- Tested and approved to EN360 standards



WORKSafe® WSFWR100 WEBBING RETRACTOR

PRODUCT CODE

710WSFWR10006/AZ011	WORKSafe® WR100 Webbing Retractor, Swivel Snap Hook, Fall Indicator, Webbing Length: 6m
----------------------------	---



WORKSafe® WSFAC080 GUIDED TYPE FALL ARRESTER WITH AC300 WORKING ROPE

WORKSafe® ROPE GRABS

- Guided-type fall arrester on a flexible anchorage line
- Made of forged aluminium alloy, lightweight at 194g
- For use with 12mm Kernmantle Polyester Rope, AC300, comes in standard lengths of 10m, 20m and 30m. Other lengths available on request
- Tested and approved to EN 353-2, EN358 and EN12841 standards

PRODUCT CODE

710WSFAC080-RD	WORKSafe® AC080 Guided Type Fall Arrester, Red
710WSFAC300-X	WORKSafe® AC300 Kernmantle Working Rope, Diameter: 12mm, Rope Length (X): 10/20/30m



WORKSafe® WSFAC010 ROPE GRAB WITH AC100 WORKING ROPE

- Guided-type fall arrester on a flexible anchorage line
- Steel rope grab for working rope of diameter 14mm
- Galvanized steel snap hook (opening: 18mm, weight: 220g)
- Energy dissipator
- Tested and approved to EN353-2 standards

PRODUCT CODE

710WSFAC010	WORKSafe® AC010 Rope Grab with Energy Dissipator, Snap Hook for Working Rope, Diameter: 14mm
710WSFAC100-X	WORKSafe® AC100 Kernmantle Working Rope, Diameter: 14mm, Rope Length (X): 10/20/30/40/50/120m



WORKSafe® WSFAC012 ROPE GRAB WITH AC100 WORKING ROPE

- Guided-type fall arrester on a flexible anchorage line
- Galvanized steel rope grab for working rope of diameter 14mm
- Tested and approved to EN353-2 standards

PRODUCT CODE

710WSFAC012	WORKSafe® AC012 Rope Grab, Galvanized Steel for Working Rope, Diameter: 14mm
710WSFAC100-X	WORKSafe® AC100 Kernmantle Working Rope, Diameter: 14mm, Rope Length (X): 10/20/30/40/50/120m



WORKSafe® WSFAC040 ROPE GRAB WITH AC200 WORKING ROPE

- Guided-type fall arrester on a flexible anchorage line
- Stainless steel rope grab for working rope of diameter 12mm
- Tested and approved to EN353-2 standards

PRODUCT CODE

710WSFAC040	WORKSafe® AC040 Rope Grab, Stainless Steel for Working Rope, Diameter: 12mm
710WSFAC200-X	WORKSafe® AC200 Kernmantle Working Rope, Diameter: 12mm, Rope Length (X): 10/15/20/30/40/50m



WORKSafe® WSFAC060 LINOSTOP II ROPE GRAB

- Guided-type fall arrester on a flexible anchorage line
- Stainless steel rope grab and kernmantle polyamide working rope of diameter 12mm and length in 5m/10m/15m/20m/25m/30m/35m/40m/45m/50m
- Galvanized steel snap hook (opening: 18mm, weight: 220g)
- Energy dissipator

PRODUCT CODE

710WSFAC060-XX	WORKSafe® AC060 Linostop II Rope Grab with Energy Dissipator, Snap Hook with Working Rope, Diameter: 12mm, Rope Length (XX): 05-50m
-----------------------	---

- Tested and approved to EN353-2 standards





WORKSafe® CONFINED SPACE SYSTEMS



- Working load limit: 500kg and breaking force: 22kN
- Zinc-plated, painted steel head with four anchor points
- Aluminium adjustable legs, come with webbing and chain to prevent legs spreading and collapsing
- Weight: 14.3kg with webbing, 17.3kg with chain
- Tested and approved to EN795 standards
- Height: 147 to 229cm
- Diameter: 119 to 182cm

PRODUCT CODE

710WSFAT011	WORKSafe® AT011 Safety Tripod, with Webbing and Chain
--------------------	---

(Tripod Bag 710WSFAX016 available for purchase separately)

WORKSafe® WSFAT050 RESCUE LIFTING DEVICE



- Rescue lifting and lowering device
- Automatic brake
- Steel galvanized cable of diameter 6.3mm
- Available in 20m and 25m length
- Weight: 13kg
- Working load: 180kg and breaking force: 1,800kg
- Tested and approved to EN1496 Class B standards

PRODUCT CODE

710WSFAT050-20/25	WORKSafe® RUP 502 Rescue Lifting Device AT050, Galvanized Steel Cable Diameter: 6.3mm, Cable Length: 20m/25m
--------------------------	--

WORKSafe® FALL PROTECTION CONNECTORS



- Gate opening: 18mm
- Weight: 80g
- Tested and approved to EN362 and SS528: Part 5 standards (TÜV SÜD PSB-approved)

WORKSafe® ALUMINIUM TWIST-LOCK KARABINER WSF320 (TÜV SÜD PSB)

PRODUCT CODE

710WSF320	WORKSafe® Aluminium Twist-lock Karabiner, Silver Blue (TÜV SÜD PSB-approved)
------------------	--

WORKSafe® ANCHORAGE CONNECTORS



- Anchor sling suitable for almost all types of structures
- Made of 20mm-width polyamide webbing
- Static strength: 22kN
- Comes in standard lengths of 1.2m or 2m; other lengths available on request, up to a maximum of 2m
- Tested and approved to EN354 and EN795 Class B standards

WORKSafe® WSFAZ900 WEBBING SLING

PRODUCT CODE

710WSFAZ900120	WORKSafe® Webbing Sling, Red, Length: 1.2m
710WSFAZ900200	WORKSafe® Webbing Sling, Red, Length: 2m



- Anchor sling suitable for rounded smooth surfaces
- Made of 45mm-width polyamide/polyester webbing with zinc-plated D-rings sewn on each end
- A synthetic rubber band is sewn on the webbing for extra grip
- Static strength: 22kN
- Comes in standard lengths of 1.4m or 2m; other lengths available on request, up to a maximum of 2m

- Tested and approved to EN354 and EN795 Class B standards

PRODUCT CODE

710WSFAZ700-1.4M	WORKSafe® Webbing Sling, Blue, Length: 1.4m
710WSFAZ700-2M	WORKSafe® Webbing Sling, Blue, Length: 2m





WORKSafe® WSAZ500 WEBBING SLING

- Anchor sling suitable for rounded smooth surfaces
- Made of 44mm-width polyester webbing with zinc-plated D-ring sewn on one end, and a self-closed loop sewn on the other end
- Static strength: 22kN
- Comes in standard length of 1.8m; other lengths available on request, up to a maximum of 5m

- Tested and approved to EN354 and EN795 Class B standards

PRODUCT CODE

710WSFAZ700-1.8M | WORKSafe® Webbing Sling,
Lime Green, Length: 1.8m

710WSFAZ500-5M | WORKSafe® Webbing Sling,
Lime Green, Length: 5m



WORKSafe® ANCHORAGE CONNECTORS

WORKSafe® WSAZ410 STEEL CABLE CONNECTING LANYARD

- Steel cable anchorage connector with plastic cable protector
- Suitable for structures with sharp edges
- Static strength: 15kN
- Tested and approved to EN795 Class B standards
- Karabiner sold separately

PRODUCT CODE

710WSFAZ410-1 | WORKSafe® AZ410 Steel Cable
Connecting Lanyard, Length: 1m



WORKSafe® WSFAT250 ALUMINIUM ANCHOR CLAMP

- Lightweight (1.37kg) aluminium I-beam anchor clamp
- Adjustable, fits I-beams of width 95mm to 400mm
- Dimensions: 440 x 100 x 45mm
- Designed for 1 worker
- Tested and approved to EN795 Class B standards

PRODUCT CODE

710WSFAT250 | WORKSafe® AT250 Aluminium Anchor
Clamp, For 1 worker only



WORKSafe® AT061 ALUMINIUM ANCHOR BEAM AND BAG

- Lightweight (3.2kg) aluminium anchor beam
- Adjustable width from 300mm to 1,270mm
- Designed for 1 worker
- Comes with a convenient carrying bag for mobility
- Tested and approved to EN795 Class B standards

PRODUCT CODE

710WSFAT061 | WORKSafe® AT061 Aluminium Anchor
Beam, Carry Bag, For 1 worker only



WORKSafe® HORIZONTAL ADJUSTABLE WEBBING WITH RED SLING BAG AND SNAP HOOK

- Temporary horizontal adjustable webbing lifeline that comes with a ratchet tensioner and snap hook on each end for quick and easy installation
- Webbing length: 10m or 20m
- Webbing width: 35mm
- Has connecting webbing sewn to bag to stow excess webbing
- Allows up to 3 workers at the same time
- Tested and approved to EN795 Class B standards

PRODUCT CODE

710WSFAE320-10-50-60 | WORKSafe® Horizontal
Adjustable Webbing, 10m,
Red Sling Bag, 2 Snap Hooks

710WSFAE320-20-50-60 | WORKSafe® Horizontal
Adjustable Webbing, 20m,
Red Sling Bag, 2 Snap Hooks



WORKSafe® TEMPORARY HORIZONTAL LIFELINES



- Prevents accidental tool drops when working at height
- Lanyard conveniently attaches to belt or harness

PRODUCT CODE

710WSFAY002 | WORKSafe® Tool Lanyard

